



EAGLE BRIDGES PRODUCT DATA

PRODUCT: RHINO-GUARD U/L BLACK

Product Number: 3412-07

DESCRIPTION: RHINO GUARD U/L BLACK IS A SOLVENT BASED PROTECTIVE COATING THAT CAN BE USED IN A VARIETY OF APPLICATIONS SUCH AS: UNDER CARRIAGE COATING FOR TRUCKS AND TRAILERS, VAPOR BARRIER FOR BURIAL VAULTS, ANY APPLICATION WHERE A THICK FLEXABLE FILM IS REQUIRED.

PROPERTIES	APPLICATION
<p>VISCOSITY: THIXOTROPIC HEAVY BODY</p> <p>POUNDS PER GALLON: 11.17 +/- .2</p> <p>GLOSS: DULL FLAT FINISH</p> <p>FLASH POINT: 50 DEGREES F+</p> <p>VOLATILE ORGANIC COMPOUND (VOC) 3.25 LBS PER GALLON</p> <p>SOLIDS: by volume (+/-) 2% - 49.19</p> <p style="padding-left: 40px;">by weight (+/-) 2% - 70.93</p> <p>THEORETICAL COVERAGE @ 1 mil dry: 788.98 sq. ft. per gallon. No loss assumed.</p> <p>FLEXABILITY: EXCELLENT</p> <p>IMPACT RESISTANCE: GOOD</p> <p>ADHESION: EXCELLENT</p> <p>HEAT RESISTANCE : SOFTENS</p> <p>HUMIDITY RESISTANCE: EXCELLENT</p> <p>WATER IMMERSION: EXCELLENT</p> <p>SALT SPRAY RESISTANCE: EXCELLENT</p>	<p>PREPARATION: Apply to properly cleaned or treated surface. This may consist of solvent wiping, wire brushing, sandblasting, phosphate treatment or chemical etching.</p> <p>TYPE OF APPLICATION: AIRLESS SPRAY OR PRESSURE POT.</p> <p>REDUCTION: NONE NECESSARY</p> <p>REDUCING SOLVENT: MINERAL SPIRITS</p> <p>REDUCED VISCOSITY ; N/A</p> <p>RECOMMENDED DRY FILM: 6-10 mils</p> <p>RECOMMENDED PRIMER: NONE</p> <p>CLEAN-UP SOLVENT: NAPHTHA OR MINERAL THINNER.</p> <p>DRY TIME: 30 MINUTES DEPENDING ON HUMIDITY AND TEMPERATURE. DRIES TO TACKFREE AND BLOCK RESISTANT FILM IN A FASTER TIME THAT CONVENTIONAL UNDERCOATERS.</p>

This information is offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommendations are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use.

Custom Engineered Industrial Paints, Coatings and Adhesions
P.O. Box 496 Byron, Georgia 31008, 478-956-5605 Fax: 478-956-3617